

# Mooring buoys

The use of mooring buoys meets different purposes like:

- Reducing anarchic mooring of cruise ships and yachts at anchor in protected areas
- Offshore & remote mooring
- Temporary mooring in a port, dock or harbour
- Additional mooring for large vessels on berthing/ mooring dolphin
- Long term mooring for occasionally used vessels.

It is sized to the characteristics of the civil and/or national navy boats it accommodates, the mooring line is calibrated according to environmental conditions (sea currents and exposure to the wind), it connects the mooring buoy to the dead body fixed to the bottom of the sea. VEOS Marine & Offshore design office advises you and offers you a turnkey solution.



# Mooring buoys

The mooring buoy is equipped with fixing accessories at customer's choice.

- Padeye
- Elbow crucifix
- Crucifix

And also options such as:

- Footrest
- Handrail

Standard range			
Buoyancy (Te)	Len (mm)	OD (mm)	Overall Length (mm)
5	1325	2500	2300
7,5	1325	3000	2300
10	1325	3500	2300
15	1500	3950	2475
20	2000	3900	2975
25	2000	4350	2975
30	2500	4200	3475



ZONE FINALENS - DOUVRIN  
62091 HAINES CEDEX FRANCE

Tel : +33 (0)3.21.26.88.88  
E-mail : contact@veos.fr